PT-XYP-200 Automatic Shrinkable Label Inserting Machine 全自動立式自動套標籤機

1. 功率 Power（kw）	3 KW
2. 電壓 Voltage（v）	220 V AC
3. 生產適度 Production Rate（b/min）	MAX200（標籤長度Label length 70mm以下 the following）
4. 適用瓶身直徑範圍 Range of bottle diameter（mm）	Φ30—Φ90 mm
5. 適用標籤長度 Label insertion length（mm）	30~220 mm
6. 適用標籤厚度 Range of label thickness（mm）	0.03~0.13 mm
7. 適用紙管內徑 Paper core inner diameter（mm）	5”~10”自由調整Free adjustment
8. 外形尺寸 Overall dimensions（mm）	2100L x 900W x 2000H mm
9. 重量 Weight（kg）	280 kg
10. 驅動方式 Drive mode	單驅Single drive

本公司基於研究改進之必要，因此保有外觀尺寸規格等修改之權利。
All specification and design characteristics shown in this catalogue are subject to change without notice.



各種標籤套入法

Various label insertion methods operated by PT-XYP series shrinkable label inserting machines



CAP SEALING TYPE 瓶口型

OVERALL BOTTLE TYPE 整瓶型

FULL BODY LABELING TYPE 瓶身到底型

MIDDLE BODY LABELING TYPE 瓶身中間定位型

旭源包裝科技股份有限公司

PVC PE PET PP OPS OPP BOPP 熱收縮膜（管、套、袋）
彩色印刷收縮商標／全自動套標籤機
食品／工業及其他複合軟性包裝

http://www.xuyuanpack.com
E-mail:info@xuyuanpack.com

TAIWAN HEADQUARTER AND MANUFACTURE PLANT
305046 新竹縣新埔鎮巨埔里3鄰新龍路98巷33弄10號
No.10, Aly. 33 ,Ln. 98, Xinlong Rd., 3rd Neighborhood, Jupu Vil. Xinpu Township, Hsinchu County 305046, Taiwan(R.O.C.)
TEL：+886-3-5982727 FAX：+886-3-5982738

CHIAYI Fab.
622011 嘉義縣大林鎮大美里大埔美園區二路7號
No.7, Yuanqu 2nd Rd., Dapumei, Damei Village, Dalin Township, Chiayi County 622011, Taiwan(R.O.C.)
TEL：+886-5-2952888 FAX：+886-5-2952999

INDONESIA Site Office
TEL : +62-21-89904402 (REP) FAX : +62-21-89908323

SHANGHAI Site Office
TEL : +86-21-36536830 (REP) FAX : +86-21-36536827

USA Site Office
TEL : +01-501-492-3893 (REP)

BRAZIL Site Office
TEL : +55-14-3845-1965 (REP)

INDIA Site Office
TEL : +91-97691-10133

PT-XYP-200
Automatic Shrinkable Label Inserting Machine
全自動立式自動套標籤機



XU YUAN PACKAGING TECHNOLOGY., LTD.

PT-XYP-200

Automatic Shrinkable Label Inserting Machine

全自動立式自動套標籤機

產品特性介紹

1. 驅動機構：本機構是一種新型的熱收縮套標機的驅動裝置，自動定心、四輪衡壓的一種裝置。達到了流暢、穩定、快速的送標目的。
2. 電器配置說明：此機型套標機所採用的電器均為進口配置，採用高速定位模組、進口伺服電機、伺服驅動器、伺服控制器，全自動調整、人性化操作。
3. 套標品種類型：此機型速度在200瓶/分鐘，適用於各種瓶型的果汁、茶飲料、乳製品、純淨水、調味品、啤酒、運動飲料等食品飲料行業。
4. 採用進口觸摸彩屏。機器可在同一限速上運行，不存在倒瓶、漏標的現象。

Product Features

1.Drive Mechanism: The mechanism of this machine is a novel driving device for a heat-shrink labeling machine, automatically aligning and exerting four-wheel pressure. It achieves smooth, stable, and rapid labeling.

2.Electrical Configuration Explanation: The electrical components utilized in this labeling machine are all imported, incorporating high-speed positioning modules, imported servo motors, servo drivers, and servo controllers, enabling automatic adjustments and user-friendly operations.

3.Application Variety: With a speed of 200 bottles per minute, this machine is suitable for various bottle types in the food and beverage industry, including juices, teas, dairy products, purified water, condiments, beer, sports drinks, and more.

4.Equipped with an imported touch screen, the machine can operate at the same speed limit without issues such as bottle overturning or mislabeling.



