XYL-600 Automatic Shrinkable Label Inserting Machine 全自動立式自動套標籤機

1. 功率 Power (kw)	2 KW
2. 電壓 Voltage (v)	3P / 220V~ 415V
3. 生產速度 Production Rate (b/min)	600 BPM(標籤長度180mm, label length 180mm)
4. 適用瓶身直徑範圍 Range of bottle diameter (mm)	Ø25 ~ Ø130
5. 適用標籤長度 Label insertion length (mm)	25 ~ 300 mm
6. 適用標籤厚度 Range of label thickness (mm)	0.035~0.08 mm
7. 外形尺寸 Overall dimensions (mm)	1190L x 1350W x 2000H mm

本公司基於研究改進之必要，因此保有外觀尺寸規格等修改之權利。
All specification and design characteristics shown in this catalogue are subject to change without notice.



各種標籤套入法

Various label insertion methods operated by XYL series shrinkable label inserting machines



瓶身到底型
FULL BODY LABELING TYPE



瓶身中間定位型
MIDDLE BODY LABELING TYPE



整瓶型
OVERALL BOTTLE TYPE



瓶口型
CAP SEALING TYPE



背套型
CAP LABEING TYPE

旭源包裝科技股份有限公司

PVC PE PET PP OPS OPP BOPP 熱收縮膜（管、套、袋）
彩色印刷收縮商標／全自動套標籤機
食品／工業及其他複合軟性包裝

http://www.xuyuanpack.com
E-mail:info@xuyuanpack.com

TAIWAN HEADQUARTER AND MANUFACTURE PLANT
305046 新竹縣新埔鎮巨埔里3鄰新龍路98巷33弄10號
No.10, Aly. 33 ,Ln. 98, Xinlong Rd., 3rd Neighborhood, Jupu Vil. Xinpu Township, Hsinchu County 305046, Taiwan(R.O.C.)
TEL：+886-3-5982727 FAX：+886-3-5982738

CHIAYI Fab.
622011 嘉義縣大林鎮大美里大埔美園區二路7號
No.7, Yuanqu 2nd Rd., Dapumei, Damei Village, Dalin Township, Chiayi County 622011, Taiwan(R.O.C.)
TEL：+886-5-2952888 FAX：+886-5-2952999

INDONESIA Site Office
TEL : +62-21-89904402 (REP) FAX : +62-21-89908323

SHANGHAI Site Office
TEL : +86-21-36536830 (REP) FAX : +86-21-36536827

USA Site Office
TEL : +01-501-492-3893 (REP)

BRAZIL Site Office
TEL : +55-14-3845-1965 (REP)

INDIA Site Office
TEL : +91-97691-10133

XYL-600
Automatic Shrinkable Label Inserting Machine
全自動立式自動套標籤機



XU YUAN PACKAGING TECHNOLOGY., LTD.

XYL-600

Automatic Shrinkable Label Inserting Machine

全自動立式自動套標籤機

產品特性介紹

1. 透明化外觀採不鏽鋼包覆式設計，符合機械設計規範，單一機體安裝方便。
2. PC控制系統設計。
3. 人機介面控制系統，更貼近人性化操作。
4. 節能減碳化機構設計，全機耗能僅1KW。
5. 膜料供料設計，可依據產線的需求採用不同的供料系統。
6. 內建設備預防保養系統。

Product Features

1.Clear image design constructed by stainless steel. Comply with safety regulation. Simplex machine structure ensures convenient installation.
2.PC base controller.
3.Interface touch controller for user-friendly operation.
4.Machnical design conform to Energe saving. Power consumtion only 1KW .
5.According to production line requirment provide to suitable label feeding system.
6.Pre maintenance system initiate desing.

